



AMERICAN CAR CRAFT INSTRUCTION

**CHALLENGER BRUSHED SHIFTER PLATE  
PART#151001**



**INCLUDES:**

- 1-Tube of promoter
- 1-Base plate
- 1-Trim ring

**!!!!!!VERY IMPORTANT!!!!!!**

BEFORE YOU BEGIN YOU MUST FIRST PREP YOUR DASH/DOOR AREAS WHERE PIECES ARE GOING TO BE INSTALLED IN ORDER TO ALLOW ADHESION!!!! You can do this by scrubbing the entire area first with household isopropyl alcohol. **NOTE: If these areas have been treated with armor all or any such surface protector; installation will NOT work unless these treatments have first been removed using special chemicals, Such as 5900. It is critical to do this because the tape will not stick to any surface that has a armor all on it.**

**We can not be responsible for kits not sticking do to improper preparation!**

**PLEASE NOTE: Installation errors are NOT manufacturing defects and parts can NOT be RETURNED due to improper installation.**

1. Once your areas have been prepared use the adhesive promoter tubes (provided) to wipe the areas of your dash/door that will be covered with your new stainless pieces. Allow a few seconds to dry. **You have been provided with attachment tape test strips. Use one of these to test the tack. If it seems to stick well then you can proceed with your installation.**
2. Your new part comes with two pieces, one base plate and a trim ring that's goes around the edge of the base plate. By centering the base plate around the holes for P,R,N,D..The gap around the edge will not be the same all the way around due to the flexibility in the plastic should that the shifter plate is centered in..This is where the ring comes in hand and you use that to finish off the edges of the part so that it looks finished..
3. **IMPORTANT!!** Before you remove the liner for permanent attachment place each piece into position and check the fit and also get acquainted with just how each part sets in place. It WILL be necessary to form a few of the parts by hand to CONFORM to the shape of your center console to insure a nice perfect fit without forcing the shape. Once you are satisfied with the shape and fit peel the red release liner and firmly press each piece into position.

**Note:** EXTRA CARE must be taken when cleaning your dash kit. It is a good idea to lightly dust your kit with a clean soft cloth first in order to prevent any particles from scratching it. Then wipe (using a new clean soft cloth) with a good quality streak free glass cleaner.

**If any questions occur during installation please contact American Car Craft @ 727-861-1500**

**Thank you and enjoy your purchase!**

AMERICAN CAR CRAFT  
18924 SAKERA RD HUDSON FL 34667  
Phone: 727 861-1500 Fax: 727 861-1520  
[www.americancarcraft.com](http://www.americancarcraft.com)