



DARE 2B DIFFERENT! ENTERPRISES LLC ®

Inventory	
A	Replacement Hatch Handle
B	Plastic Clips (2)
C	Powder Coated Lock Nuts (3)
D	Black Center Bolt
E	Tag Your Hatch Handle Cards

xB/bB Replacement Hatch Handle Installation Instructions

Tools Required
Phillips Screwdriver
Interior Panel Clip Removal Tool
Ratchet
10mm Deep Socket
Needle Nose Pliers

Helpful hint: You can make your own panel clip tool with a four prong fork and pliers. Using the pliers bend the two middle prongs back and forth until they snap off. With the center prongs removed you have created your own panel tool.

Install Time: Approximately 20 minutes

- 1) First remove the felt inner hatch panel with your tool of choice by placing the center of your tool under the panel clip (button) and prying in an up and out movement. Save the button(s) or if they break from being too brittle you can buy a pack of ten at any automotive parts store. .
- 2) Using the 10mm deep socket and/or Pliers remove the 3 old lock nuts, studs and clips holding the garnish to the hatch panel and dispose of them (replacement hardware is included)
- 3) Remove the old hatch handle from the car
- 4) Once the handle is free from the car using the Phillips Screwdriver remove the two retaining screws on the touch pad. **(Do not lose them you are reusing them)**
- 5) The touch pad will still be held in place by two retaining clips. Gently squeeze these with the needle nose pliers one at a time to remove touch pad from handle.
- 6) **You do not have to disconnect any of the wiring**
- 6) Locate the keyhole shaped slot on the left underside of the handle and snap the provided **BLACK STUD'S** square head into this slot.
- 7) Locate the square slotted hole to the right of the stud and snap the new plastic clip into this hole.
- 8) Re-install your lights and touch pad into the new handle and run your wires back into the retaining channel.
- NOTE: DO NOT REMOVE THE PROTECTIVE PLASTIC FROM THE CHROME GARNISH UNTIL IT IS FULLY INSTALLED TO PROTECT THE FINISH. ALSO BE SURE TO PROTECT THE STUDS FROM DAMAGE BY EITHER TAPING THE THREADS OR PUTTING SOME SHRINK TUBE ON THEM BEFORE INSERTING BACK INTO THE BODY.**
- 9) Insert handle studs into their correct locations on the hatch panel
- 10) Install the new lock nuts on the studs and gently tight them with the 10mm socket.
DO NOT OVER TIGHTEN.
- 11) Using your plastic clips reinstall your inner felt hatch panel
- 12) For those that have purchased the chrome handle please remove the plastic coating and wax part regularly as you would your paint. For those who have a painted handle they are already hand waxed but it would never hurt to re-wax the part. This is part of normal care.

LIFETIME WARRANTY ON THE CASTING 1 YEAR WARRANTY ON THE FINISH

Tag! Your Hatch Handle Broke Game Cards are included in your package.

Please TAG! other 04-06 Scion xB owners even if their handle is not currently broken as it will break eventually.

Thank you for your assistance in helping fellow Scion xB owners.